



# STAMINA

## Indoor / Outdoor Surface Coating

### DESCRIPTION

STAMINA™ is a water-based Indoor / Outdoor hard surface sealer that provides superior resistance to moisture, grease, solvents and other foreign materials. Outstanding durability; coating will not whiten or “peel-off” surfaces. Ideal for concrete, terra cotta, brick, pavers, saltillo tiles, as well as a wide variety of unglazed ceramic tiles. Can achieve a high gloss in as few as 2 coats!

### PRODUCT FEATURES / BENEFITS

- Easy to Apply / Saves time, labor and reduces training requirements
- Fast Drying / Recoat quickly to save time.
- UV Resistant / Great for outdoors or areas in direct sunlight.
- Low odor formulation / Excellent for both indoors and outdoors.
- Eliminates need for surface etching / saves time and labor
- Forms a wear resistant barrier on surface to grease, oil and soiling.
- Water resistant / Will not whiten or “peel-off” surfaces

### DIRECTIONS FOR USE

**Areas for Use:** Office Buildings, Manufacturing and Industrial Plants, Shopping Centers, Malls, Indoor / Outdoor Plazas, Parking Lots, Auto Repair Shops / Dealerships, Supermarkets and Retail Stores, Schools & Educational Facilities, Swimming Pool Surrounds, Warehousing & Storage Facilities.

**Floor Preparation for all Interior / Exterior Surface**

**Applications:** Remove all grease, oil and other foreign materials from the surface with **CONKLEEN 204** Concrete Cleaner. If previous coatings are present, remove the coating with appropriate stripper. Rinse the surface thoroughly and allow to fully dry prior to application of **STAMINA**.

**Application:** Apply **STAMINA** using a rayon or other floor finish mop, lambs wool applicator or paint roller. Apply the first coat of **STAMINA** using a thin, even coating on surface. Allow a minimum of 45 minutes drying time prior to application of additional coats.

**Routine Maintenance:** Damp mop floors with mop & bucket or clean with an automatic scrubber using appropriate NCL Neutral Floor Cleaner following label directions. For areas that require heavy cleaning or degreasing, select appropriate NCL Degreaser Cleaner following label directions. Rinse surface with water after cleaning.

### SPECIFICATIONS

Color ..... White, opaque liquid  
 Odor ..... Typical acrylic  
 pH ..... 8.1 ± 0.25  
 Drying Time (minutes) ..... 45 (minimum)  
 Coverage (sq. ft./gal) ..... 2,500  
 Specific Gravity (g/cc) ..... 1.02 ± 0.01  
 Density (lbs/gal) ..... 8.5 ± 0.1  
 Slip Resistant ..... Yes  
 Freeze Thaw Stable ..... Yes (3 cycles)

Detergent Resistant ..... Yes  
 Leveling ..... Excellent  
 Water Resistance ..... Excellent  
 Black Mark Resistant ..... Excellent  
 Scuff Resistant ..... Excellent  
 Resistant to Soiling ..... Excellent  
 Gloss Retention ..... Excellent  
 Immediate Wet Look Gloss ..... Outstanding  
 Shelf Life ..... 1 year minimum in original unopened container

### SAFETY INFORMATION

**KEEP OUT OF THE REACH OF CHILDREN.**

**Precautionary statement**

**Prevention:** Observe good industrial hygiene practices.

**Response:** Wash thoroughly after handling.

**Storage:** Store away from incompatible materials.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a “Hazardous Chemical” as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Additional safety measures:**

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at [www.nclonline.com](http://www.nclonline.com)

Meets or exceeds 0.5 coefficient of friction as measured by James Machine Methodology ASTM Method D 2047-82.

**KEEP FROM FREEZING**

For Commercial and Industrial Use Only



FLOOR CARE



401 N. 10th Street • Philadelphia, PA 19123  
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517  
[www.nclonline.com](http://www.nclonline.com) • e-mail:[info@nclonline.com](mailto:info@nclonline.com)