



SUPER-SONIC

Intensive Speed Stripper

DESCRIPTION

A breakthrough formulation for all stripping applications. Utilizing exclusive AST. technology, this product liquifies floor finish build-up with unbeatable speed! It may be used on vinyl composition tile, vinyl tile and other resilient floors. SUPER-SONIC. is also ideal for terrazzo and many other non-resilient surfaces.

PRODUCT BENEFITS

- AST. technology promotes exceptionally rapid liquification of floor finish
- Thoroughly emulsifies even multiple layers of burnished floor finish easily
- Controlled foaming, saves time and labor
- Highly active formula allows for product to be used at higher dilution ratios; saves product cost

DIRECTIONS FOR USE

Mop/Wet Vacuum Stripping System:

Follow the dilution chart below (in cold or mildly warm water):

Light/Medium Duty Build-Up:

.....Dilute 1 part SUPER-SONIC to 16 parts water.

Heavy Duty Build-Up:

.....Dilute 1 part SUPER-SONIC to 5 parts water.

Apply liberally with a mop to an area small enough so as not to allow the product to dry and allow to stand for 3 to 5 minutes. Agitate with a mop and remove solution and old finish with a wet vacuum. Allow floor to dry thoroughly and apply new finish as directed by manufacturer. If complete stripping is not accomplished repeat the above procedure before re-application of recommended NCL Floor Finish.

Floor Machine Stripping System: Follow the dilution chart below (in cold or mildly warm water):

Light/Medium Duty Build-Up:

.....Dilute 1 part SUPER-SONIC to 16 parts water.

Heavy Duty Build-Up:

.....Dilute 1 part SUPER-SONIC to 5 parts water.

Allow to stand for 3 to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Remove solution and old finish with a wet vacuum and allow floor to dry completely. If desired, a rinsing step can be added. Apply recommended NCL Floor Finish as per instructions.

Note: Asphalt tile, Linoleum, and other sensitive floor surfaces may be damaged by contact with stripping solution. We recommend that a spot test be conducted before general use.

SPECIFICATIONS

Evaporation Rate = To Water
 Solubility In Water Complete
 Specific Gravity (g/cc)..... 1.01 ± 0.01
 Upper Cloud > 140°F
 Lower Cloud < 34°F
 pH 13.6 ± 0.4

Freeze Thaw Stable
 Hard Water Stable
 Appearance Clear, Thin Liquid
 Odor Mild characteristic
 Boiling Point 212 °F (100 °C)
 Shelf Life 2 years minimum in original unopened container

SAFETY INFORMATION

DANGER: HARMFUL IF SWALLOWED. CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. HARMFUL IF INHALED. MAY CAUSE RESPIRATORY IRRITATION. KEEP OUT OF THE REACH OF CHILDREN.



Precautionary statement

Prevention: Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response: If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents/container in accordance with local authority requirements.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

For Commercial and Industrial Use Only



Stripper



401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com