



WITHSTAND

*Non-Buff Maximum Wear
Sealer / Finish*

DESCRIPTION

This superior sealer / finish is ideal for areas which receive little to no polishing or buffing. Utilizing MPS77 Advanced Technology, WITHSTAND provides a dramatic wet-look gloss from fewer coats, with long term gloss retention. Easy to apply; reduces labor costs. Classified by Underwriters Laboratories® for slip resistance.

PRODUCT FEATURES / BENEFITS

- High Traffic Applicable
- Exceptional wear and durability
- Combination Sealer/Finish reduces product cost
- Maximum scuff and scratch resistance
- Reduces labor costs associated with buffing maintenance

DIRECTIONS FOR USE

Floor Preparation: Strip old finish and wax using your preferred NCL floor stripper following label directions. For baseboards and corners, use an NCL baseboard stripper following label directions. If necessary, rinse thoroughly with clean water and allow to completely dry.

Application: Using a clean mop or applicator apply a thin uniform coats of WITHSTAND™ Non-Buff Floor Sealer / Finish. Allow to dry for a minimum of 20 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

High Speed Buffing and Burnishing (if desired):

WITHSTAND™ Non-Buff Floor Sealer / Finish is an ideal product for use in areas where minimal or no buffing maintenance can be performed. You may, if desired, maintain this product with High Speed polishing or UHS burnishing equipment (electric, battery or propane). Conventional speed maintenance is not recommended. Prior to buffing or burnishing dust mop the floor surface using an NCL dust mop treatment. Buff or dry burnish using an approved buffing pad. For spray buffing, mop-on or autoscrubber restoring use a preferred NCL gloss restorer.

Routine Maintenance: Dust mop using mop treated with an NCL dust mop treatment. Damp mop or clean with an automatic scrubber using your preferred NCL neutral floor cleaner following label directions.

SPECIFICATIONS

| | | | |
|-----------------------------|-----------------------|----------------------|---|
| Type..... | Pure acrylic polymers | Film Appearance..... | Clear |
| pH..... | 8.5 ± 0.5 | Powdering..... | None |
| Drying Time (minutes) | 30 | Flash Point..... | None |
| Color..... | White, opaque liquid | Slip Resistant..... | Yes |
| Odor..... | Typical acrylic | Shelf Life..... | 1 year minimum in original unopened container |

SAFETY INFORMATION

KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash thoroughly after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING

For Commercial and Industrial Use Only



FLOOR CARE



Floor Coating and Finishing Material
As to Slip Resistance Only
18EL



World Class Cleaning & Hygiene Solutions™

401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com



TDS-0591-0623